

# Tewkesbury White Door

## Painting Instruction



To provide a unique kitchen style, the Tewkesbury White range can be painted by trade professionals.


### Tools & Products Required



Eye Protection



Dust Mask




Sand Paper & Block  
(240/180 grit)



Undercoat  
Paint



Oil Based  
Paint\*




Brush or Roller\*\*

\*Other paint types can be used, however oil based paints are most hardwearing and durable.


\*\*Mohair rollers are recommended for the best finish. These are available from decorators merchants.

### Door Preparation



- Ensure doors are detached from units before door preparation is started.
- Lightly sand the door along the grain on both sides using a 240 or a 180 grit sandpaper to ensure there is a suitable key for painting.
- Ensure the door is sanded evenly by hand (using an electric sander may result in an uneven finish and could damage the door).
- Do not use wire wool or other sanding materials containing steel/iron on the door.
- Remove dust and grit from the door and work the area with a damp cloth before starting to paint.

### Door Painting & Finishing



- A sealer coat may be required with some paints – please consult the paint manufacturer for more information.
- Doors should be painted in a warm, dry atmosphere that is free from dust and debris.
- If you are painting a glass door, ensure you mask around the glass before you start painting.
- If you are using an oil based paint, an undercoat mixed to the same colour as the door should be used.
- Using roller or brush paint the door - making sure to avoid drips and runs.
- The following painting sequence should be followed for the best finish:
  - Internal edge profile
  - Centre panel
  - Horizontal rails
  - Vertical rails
- Ensure the paint fills the V groove in the door. Additional coats may be required to achieve the desired finish.
- Since the doors are in close proximity to each other, it is important that they are painted in the same way to ensure a consistent finish.
- Decorative accessories (e.g. cornice, pelmet, plinth and décor ends) should be prepared in a similar way to the doors and fully painted before fitting. Touching up will be required around the joints once installed.
- Doors should be stored in a warm, dry area when drying.
- Drying times should be in accordance with the paint manufacturers recommended guidelines.

For all aspects of kitchen installation, please follow the kitchen installation manual available from your local depot.

#### Product Warranty

Tewkesbury White frontals and associated timber décor accessories (cornice, pelmet, plinth and décor ends) are guaranteed for 5 years against manufacturing defects & workmanship relating to the construction and structural performance of the product during normal domestic use.

The performance and durability of the painted/lacquered surface which has been subjected to additional preparation or application of alternative coatings or finishing are not covered by guarantee.